



CONNECTION INFORMATION

CONTROL IN CINIA TON							
CONNECTION					MAKE-UP	TENSILE	TORSIONAL
	1		T		TORQUE	STRENGTH	STRENGTH
SIZE	TYPE	I.D.	O.D.	STRENGTH	(FT-LBS)	(POUNDS)	(FT-LBS)
2''	I.F.	1"	2-5/8''	?	1,800	62,450	2,500
2-3/8"	REGULAR	1"	3-1/8''	BOX	3,000	344,416	5,329
	I.F.	1-3/4"	3-3/8"	BOX	3,700	287,541	6,508
	I.F.	2''	3-1/2"	BOX	3,200	206,500	4,568
2-7/8''	REGULAR	1-1/4''	3-3/4"	BOX	5,760	452,661	10,148
	I.F.	2-1/8''	4-1/8''	BOX	6,100	409,869	10,808
3-1/2"	REGULAR	1-1/2''	4-1/4''	PIN	7,900	639,916,	13,879
	I.F.	2-11/16''	4-3/4''	PIN	9,400	538,366	16,565
4-1/2"	REGULAR	2-1/4''	5-7/8''	BOX	21,749	1,110,344	38,278
	I.F.	2-13/16"	6-7/8''	BALANCED	32,000	1,392,400	56,807
5-1/2"	FULL HOLE	2-13/16"	7-11/16''	BALANCED	47,700	1,690,209	76,410
6-5/8''	REGULAR	2-13/16"	7-7/8''	BALANCED	53,000	1,834,534	85,354
		2-13/16"	8''	BOX	53,000	1,834,534	85,354
		3"	7-7/8''	BALANCED	50,000	1,748,938	81,126
		3"	8''	BOX	50,000	1,748,938	81,126
7-5/8''	REGULAR	2-13/16"	9-1/4''	BOX	91,633	2,747,418	146,612
		2-13/16"	9-1/2''	BOX	91,633	2,747,419	146,612
		3"	9-3/16"	BALANCED	88,000	2,661,823	141,728
		3"	9-1/4''	BOX	88,000	2,661,823	141,728
		3-1/4''	9-3/16"	BALANCED	83,000	2,539,104	134,753
		3-1/4''	9-1/2''	BOX	83,000	2,539,104	134,753