

Hunting - Drill stem specifications and dimensional information.

	Thread	Tool Joint OD (mm)	Tool Joint ID (mm)	Pipe OD (mm)	Pipe Length (cm) Shoulder-To-Shoulder	Overall Length (cm)	Torque (Nm)	Bend Radius (m)	% Slope Per Rod	Drill Stem Part Number	CMW Cross Reference
HIWS1	#200	47.6	19.1	33.4	149.9	154.9	1356	17.5	9.9%	HI222062	355-1119
	#200	47.6	19.1	33.4	182.9	188.0	1356	17.5	9.9%	HI222394	355-1120
	#200	47.6	19.1	42.2	182.9	188.0	2034	29.1	6.2%	HI216492	355-1121
	#200	47.6	19.1	42.2	304.8	309.9	2034	29.1	10.5%	HI219006	355-1122
	#250	54.0	19.1	48.3	304.8	311.2	3118	30.1	10.2%	HI230993	355-1123
	#400	57.2	22.2	52.3	304.8	311.2	3661	31.1	9.8%	HI221628	355-1124
	#600	66.7	22.2	60.3	304.8	311.2	5694	33.0	9.3%	HI222276	355-1118
	#600	66.7	22.2	60.3	457.2	463.6	5694	33.0	13.9%	HI222455	355-1126
	#650	69.9	25.4	60.3	304.8	311.2	7457	33.0	9.3%	HI296309599	355-1127
	#650	69.9	25.4	60.3	457.2	463.6	7457	33.0	13.9%	HI296312531	355-1128
	#700	78.7	31.8	66.7	304.8	312.4	8135	44.2	6.9%	HI296309521	355-1129
	#700	78.7	31.8	66.7	457.2	464.8	8135	44.2	10.4%	HI296309522	355-1130
	#900	82.6	31.8	73.0	304.8	313.7	12609	51.4	5.8%	HI222451	355-1131
	#900	82.6	31.8	73.0	457.2	466.1	12609	51.4	8.7%	HI222452	355-1132
	#800	92.1	38.1	88.9	457.2	466.1	16270	60.2	7.5%	HI222454	355-1133
#1000	111.1	57.2	88.9	609.6	466.1	20337	60.2	7.5%	HI296337977		
#1000	111.1	57.2	88.9	609.6	618.5	20337	60.2	10.2%	HI296309520	355-1134	
HXT	#402	63.5	28.6	52.4	304.8	311.8	4474	31.1	9.8%	HI281600	355-1135
	#602	69.9	31.8	60.3	304.8	311.8	6779	33.0	9.3%	HI294566	355-1136
	#602	69.9	31.8	60.3	457.2	464.2	6779	33.0	13.9%	HI284153	355-1137
	#602	71.1	31.8	66.7	457.2	464.2	6779	44.2	10.4%	HI294642	355-1138
	#702	85.7	38.1	66.7	449.6	458.5	9491	44.2	10.0%	HI276305	355-1139
	#902	98.4	50.8	73.0	457.2	466.1	17626	51.4	8.9%	HI276307	355-1140
	#802	104.8	57.2	88.9	609.6	618.5	24405	60.2	10.1%	HI276376	355-1141
	#802	104.8	57.2	88.9	457.2	466.1	24405	60.2	7.5%	HI350802015	355-1142
TORO/ASTECC	DD65	47.6	19.1	33.4	149.9	154.9	1220	17.5	9.9%	HI222062	
	DD2024	57.2	22.2	52.3	304.8	311.2	3525	31.1	9.8%	HI221628	
	DD3238	66.7	22.2	60.3	304.8	311.2	5423	33.0	9.3%	HI222276	
	DD4045	69.9	31.8	60.3	304.8	311.8	6779	33.0	9.3%	HI294566	
Ditch Witch® Forged	1.94-4	66.7	16.5	54.0	304.8	312.4	2983	33.2	9.2%	355-1106	JT20
	2.11-4	70.1	22.6	60.3	299.1	307.3	5423	37.5	8.0%	355-1244	JT25 / JT30
	1.94-4	66.7	16.5	54.0	304.8	312.4	2983	33.2	9.2%	355-1106	JT20 Lined
	2.11-4	70.1	22.6	60.3	299.1	307.3	5423	37.5	8.0%	355-1244	JT25_30 Lined
	2.10-4	79.4	33.0	72.0	457.2	464.8	7457	44.5	10.3%	359-1211	JT40
AT Pipe	3.44-4	114.3	53.8	92.2	430.5	443.7	16270	62.5	6.9%	355-1050-500	AT100

Updated June 2018